

Coordinated Active Perception and Manipulation of a Payload with Unknown Center-of-Mass Location

Micah Corah and Nathan Michael

I. INTRODUCTION AND METHODOLOGY OVERVIEW

We propose a coordinated active perception and manipulation strategy to enable a team of aerial robots to estimate the location of the center-of-mass (COM) of an object in order to enable cooperative aerial manipulation and transport. We pursue representative scenarios such as rubble removal and package delivery in the contexts of disaster response and logistics, respectively, where the total payload mass may exceed the lift capacity of individual aerial systems and the payload density distribution is not readily modeled as uniform. Fig. 1 provides a graphical overview of the proposed methodology depicting a team of small rotorcraft approaching and attaching to an object via a tether on a planar surface. A single robot attaches to the object and applies a wrench. Based on the outcome of the wrench application, a second system deploys to an appropriately chosen attachment point before similarly applying a wrench. The process is iteratively repeated until the object COM is accurately estimated.

Load suspension-based approaches such as those studied by Michael et al. [5] and Fink et al. [3] assume known payload mass and uniform density distribution in order to compute a stable vehicle deployment configuration that ensures static equilibrium during load transport. Techniques that seek to identify and adapt to load model uncertainty during flight relax these restrictive assumptions but require an initial robot deployment and loading configuration with respect to an assumed payload COM [4, 2].

We propose an incremental active perception and coordination strategy to enable the estimation of the location of the payload COM, thereby permitting coordinated manipulation and transport of payloads with non-uniform density. For the sake of presentation brevity and scope reduction, we make several simplify assumptions: (1) the total payload mass is known and less than the total lift capacity of the robot team; (2) the spatial extents of the payload are known; and (3) the payload is initially at rest on a planar surface. We discuss the relaxation of these assumptions as future work in Sect. IV.

II. FORMULATION AND APPROACH

We wish to estimate the location of the payload COM, \mathbf{q}_g , or more specifically the gravity wrench, \mathbf{w}_g , of an object with mass m that is subject to a set of frictionless contact constraints \mathcal{C} resulting in wrenches $\mathbf{w}\lambda$ with $\lambda \geq 0$ of the




Fig. 1: A team of robots estimate the gravity wrench, \mathbf{w}_g , of a payload by iteratively selecting attachment points, \mathcal{A} , and applying wrenches, \mathbf{w}_a , that lead to reduction in COM location uncertainty while preserving system static equilibrium.

form $\mathbf{w} = [\mathbf{r}_c \quad (\mathbf{q}_g - \mathbf{q}_c) \times \mathbf{r}_c]$ for contact point, \mathbf{q}_c and unit contact normal, \mathbf{r}_c . Given the assumptions of known total mass, spatial extents, and planar contact surface, we may further assume that the contact constraints are known a-priori.

Each vehicle-payload attachment is assumed to be equipped with sensors enabling load measurements along rays in wrench-space $\mathbf{w}_0 + \lambda_a \mathbf{w}_a$ for some feasible wrench, \mathbf{w}_0 , and force-normalized wrench, \mathbf{w}_a denoting measurements as $z = (\mathbf{w}_0, \mathbf{w}_a)$.

We define the critical force associated with a measurement, f_c^z , as the maximum value of λ_a for which the object remains in equilibrium. Let \mathbf{W}_C be the matrix whose columns are the set of normalized contact wrenches for each constraint in \mathcal{C} . The critical force computed along each tether is obtained via the linear program

$$\begin{aligned} f_c^z(w_g) = \arg \max_{\lambda_a} & \\ \text{s.t. } & \mathbf{w}_a \lambda_a + \mathbf{W}_C \lambda_C + \mathbf{w}_0 + \mathbf{w}_g = 0 \\ & \lambda_a \geq 0, \lambda_C \geq 0 \end{aligned} \quad (1)$$

where λ_C is a vector of contact forces and the constraints enforce static stability and feasibility conditions. We model load measurements, \hat{f}_c^z as being drawn from a Gaussian distribution such that

$$p(\hat{f}_c^z | \mathbf{w}_a, \mathbf{w}_0) = \mathcal{N}(\hat{f}_c^z - f_c^z(\mathbf{w}_g), \sigma^2) \quad (2)$$

where $\mathcal{N}(x, \sigma^2)$ is the value of the zero-mean normal pdf with variance σ^2 evaluated at x .

A. Center-of-Mass Estimation via Coordinated Active Perception and Manipulation

We formulate the COM estimation problem via a coordinated active perception framework that seeks to compute an

The authors are with the Robotics Institute, Carnegie Mellon University, Pittsburgh, PA 15213, USA. Email: {micahc, nmichael}@cmu.edu. We gratefully acknowledge the support of ARL grant W911NF-08-2-0004.

$$I_{CS}[\hat{f}_c^z; \mathbf{w}_g] = \log \frac{\int p^2(\mathbf{w}'_g) \mathcal{N}(0, 2\sigma^2) d\mathbf{w}'_g \int p^2(\mathbf{w}'_g) d\mathbf{w}'_g \iint p(\mathbf{w}'_g) p(\mathbf{w}''_g) \mathcal{N}(f_c^z(\mathbf{w}''_g) - f_c^z(\mathbf{w}'_g), 2\sigma^2) d\mathbf{w}''_g d\mathbf{w}'_g}{\left(\iint p^2(\mathbf{w}'_g) p(\mathbf{w}''_g) \mathcal{N}(f_c^z(\mathbf{w}''_g) - f_c^z(\mathbf{w}'_g), 2\sigma^2) d\mathbf{w}''_g d\mathbf{w}'_g \right)^2} \quad (4)$$




Fig. 2: Results of a simulated experiment with attachment points scaled by mutual information (blue) and the chosen attachment point (black) with active constraints, \mathbf{q}_r , denoted in red over the incrementally (left-to-right) updated belief distribution associated with the estimation of true COM location (black star).

optimal vehicle attachment point that maximizes the reduction in the uncertainty of the COM location. Similar to the coordinated active perception approach proposed by Charrow et al. [1], we compute maximally informative vehicle attachment points via an efficient analytic information measure

$$I_{CS}[\hat{f}_c^z; \mathbf{w}_g] = \log \frac{\iint p^2(\hat{f}_c^z, \mathbf{w}'_g) d\mathbf{w}'_g d\hat{f}_c^z \iint p^2(\mathbf{w}'_g) p^2(\hat{f}_c^z) d\mathbf{w}'_g d\hat{f}_c^z}{\left(\iint p(\hat{f}_c^z, \mathbf{w}'_g) p(\mathbf{w}'_g) p(\hat{f}_c^z) d\mathbf{w}'_g d\hat{f}_c^z \right)^2} \quad (3)$$

For brevity, all probabilities are implicitly conditioned on prior measurements. We then arrive at (4) after substituting the measurement model (2) into (3) and evaluating.

III. SIMULATION EVALUATION AND RESULTS

We now consider the application of the proposed methodology through a simulated scenario where a team of three robots manipulate a plate with radius $r = 1$ m, $m = 1$ kg, and measurement standard deviation $\sigma = 1$ Nm (Fig. 2). While the prior derivation applies to general object shapes, we choose to consider a simple planar shape to facilitate presentation. Further, we assume that each robot attaches and takes a single measurement and does not contribute to future wrench measurements such that the choice of attachment point directly corresponds to the choice of measurement and now refer to points directly rather than wrenches.

Assuming an initially uniform prior on \mathbf{q}_g over the convex hull of the contact points, robots iteratively select the attachment point maximizing I_{CS} via a measurement, $\mathbf{q}_a = \arg \max_{\mathbf{q} \in \mathcal{A}} I_{CS}[\hat{f}_c^z; \mathbf{q}_g]$. Fig. 2 demonstrates the belief of the COM quickly converging with the selection of attachment points.

IV. DISCUSSION AND FUTURE WORK

We propose a coordinated active perception and manipulation strategy to enable a team of aerial robots to estimate the

location of the COM of an object in order to enable cooperative aerial manipulation and transport. Individual robots apply wrenches that seek to reduce uncertainty with respect to the COM location while preserving the static stability of the load on a planar surface (through incorporation of payload-ground contact forces).

Several simplifying assumptions limit practical application of the proposed methodology including assumed knowledge of the total payload mass. We are presently addressing several of these including prior knowledge of the total payload mass and volumetric extents. Specifically, we are investigating strategies to incorporate the total mass into the belief-space formulation and model the associated uncertainty in selection of the incremental attachment points through online perception and object modeling. Additionally, we pursue an extension to the optimization formulation that allows for consideration of actuator constraints and the corresponding non-critical measurements that arise as result of achieving maximum load capacity for an individual robot. Finally, we are considering formulations that permit joint interactions by multiple robots that concurrently engage with the object.

REFERENCES

- [1] Benjamin Charrow, Sikang Liu, Vijay Kumar, and Nathan Michael. Information-theoretic mapping using Cauchy-Schwarz Quadratic Mutual Information. In *IEEE Intl. Conf. on Robot. and Autom.*, pages 4791–4798, Seattle, WA, May 2015. IEEE.
- [2] Shicong Dai, Taeyoung Lee, and Dennis S Bernstein. Adaptive control of a quadrotor UAV transporting a cable-suspended load with unknown mass. In *IEEE Conf. on Dec. and Cont.*, pages 6149–6154. IEEE, Dec 2014.
- [3] Jonathan Fink, Nathan Michael, Soonkyum Kim, and Vijay Kumar. Planning and control for cooperative manipulation and transportation with aerial robots. *Int. J. Rob. Res.*, 30(3):324–334, sep 2010.
- [4] Daniel Mellinger, Quentin Lindsey, Michael Shomin, and Vijay Kumar. Design, modeling, estimation and control for aerial grasping and manipulation. *IEEE Int. Conf. Intell. Robot. Syst.*, pages 2668–2673, 2011.
- [5] Nathan Michael, Jonathan Fink, and Vijay Kumar. Cooperative manipulation and transportation with aerial robots. *Auton. Robots*, 30(1):1–14, sep 2010.